

Vacuum Technology 2010

The Right Solution for Every Application!



Vacuum Technology





Pfeiffer Vacuum – Your ideal partner!

As a technology leader, Pfeiffer Vacuum develops high-performance, dependable products for generating and measuring vacuum. In addition, we also engineer and manufacture complete vacuum systems for you.

Your concrete needs enjoy top priority at Pfeiffer Vacuum. And this is why we offer you a complete, balanced and innovative product portfolio. With our standard products, our customer-specific solutions and, last but not least, our excellent service, we thus assist you in satisfying your individual requirements.

We are committed to two factors for our joint success: Global customer intimacy and high-technology that offers the utmost quality and perfection. And our end-to-end product line is what defines the way we see ourselves: As a competent, forward-looking, honest partner to you in developing, manufacturing and delivering the products you need.

High-quality, reliable products.
First-class service. Competent advice.

These are our strengths!

Advantages at a glance

- ▶ A leading manufacturer of vacuum technology for more than 100 years
- ▶ Inventor of the turbopump
- ▶ World market leader with approximately 300,000 turbopumps delivered to date
- ▶ Major investments in research & development
- ▶ An independent, innovative company
- ▶ A complete product line, from individual components to complex vacuum systems
- ▶ Very high standard of quality
- ▶ On-site service worldwide

Vacuum Technology





Pfeiffer Vacuum – Milestones

- 1890 Founded in Wetzlar as the “Arthur Pfeiffer” Company
- 1958 Invention of the turbomolecular pump
- 1996 Pfeiffer Vacuum Technology AG: IPO on the New York Stock Exchange
- 1997 Introduction of the first dry pump for industrial applications with convection cooling
- 1998 Second listing on the Deutsche Börse Stock Exchange in Frankfurt (today TecDax)
- 1999 Market launch of the first high-performance CompactTurbo™ 2,000 l/s class
- 2000 First line of digital gauge heads: DigiLine™
- 2005 Market launch of the OnTool™ Booster – high-vacuum pump that works against atmosphere
- 2005 Expanded product portfolio of large turbopumps with pumping speeds from 1,000 to 2,000 l/s
- 2007 Market launch of the PrismaPlus™ mass spectrometer – modular design, powerful software, wide range of applications
- 2007 Market launch of the PentaLine™ – the new two-stage rotary vane pumps
- 2008 Market launch of the HiPace™ – the new generation of turbopumps
- 2009 Market launch of the HiCube™ – The modular pumping station for clean vacuum

Quality management:
Certified under ISO 9001

Environmental management:
Certified under ISO 14001

HenaLine™ · UnoLine™ Plus

The single-stage rotary vane pumps for all low and medium vacuum applications.



General process
technology



Fluorescent tube manufacturing



Cleanroom transfer chambers





HenaLine™

Applications

- ▶ Electron beam welding
- ▶ Lamp manufacturing
- ▶ Surface coating
- ▶ Vacuum drying and degassing
- ▶ Leak detection
- ▶ Metallurgy
- ▶ Simulation chambers
(Air conditioning, aerospace)

Advantages at a glance

- ▶ A complete line of pumps with pumping speeds of between 25 and 1,000 m³/h
- ▶ Integrated oil mist separator for clean exhaust air
- ▶ Low ultimate pressure
- ▶ Compact, reliable and powerful



UnoLine™ Plus

Applications

- ▶ Transformer drying
- ▶ Cable drying
- ▶ Oil recovery
- ▶ Metallurgy
- ▶ Coating
- ▶ Chemical and process technology

Advantages at a glance

- ▶ Rugged and long-lasting
- ▶ Resistant to dust and dirt
- ▶ Bearings located outside the pumping cavity
- ▶ Extremely low speed
- ▶ Very high water vapor capacity

Technical data

Rotary vane pump	Hena 25 – Hena 1000	UnoLine™ Plus BA 251 – BA 501
Pumping speed at 50 Hz	25 – 1,000 m ³ /h	250 – 500 m ³ /h
Pumping speed at 60 Hz	30 – 1,200 m ³ /h	250 – 500 m ³ /h
Ultimate pressure without gas ballast	< 0.2 – < 0.4 mbar	< 6 · 10 ⁻² mbar
Ultimate pressure with gas ballast	< 1.5 – < 3 mbar	< 6 · 10 ⁻¹ mbar
Weight	35 – 1,080 kg	570 – 1,100 kg

DuoLine™


Two-stage rotary vane pumps with magnetically coupled drive.



Vacuum drying



Vacuum metallurgy



Coating





DuoLine™

Applications

- ▶ Coating
- ▶ Industrial
- ▶ Analytical industry
- ▶ Research & development
- ▶ Vacuum chemistry
- ▶ Vacuum metallurgy
- ▶ Vacuum drying

Advantages at a glance

- ▶ Environmentally friendly – No oil leaks
- ▶ Minimum operating costs – No shaft seal maintenance
- ▶ No exchange between process gas and the environment
- ▶ Corrosion-proof – No non-ferrous metals
- ▶ Integrated safety and gas ballast valve
- ▶ Extensive monitoring and system integration accessories
- ▶ Corrosive gas version available

Technical data


Rotary vane pump	DUO 5 M	DUO 10 M	DUO 20 M	DUO 35 M	DUO 65 M
Pumping speed at 50 Hz	5 m ³ /h	10 m ³ /h	20 m ³ /h	32 m ³ /h	62 m ³ /h
Pumping speed at 60 Hz	6 m ³ /h	12 m ³ /h	24 m ³ /h	36 m ³ /h	70 m ³ /h
Ultimate pressure without gas ballast	≤5·10 ⁻³ mbar	≤5·10 ⁻³ mbar		≤3·10 ⁻³ mbar	
Ultimate pressure with gas ballast	≤2·10 ⁻² mbar	≤1·10 ⁻² mbar		≤5·10 ⁻³ mbar	
Weight	19 kg	27 kg	33 kg	56 kg	65 kg

Rotary vane pump*	DUO 2.5	DUO 35	DUO 65	DUO 125	DUO 255
Pumping speed at 50 Hz	2.5 m ³ /h	32 m ³ /h	62 m ³ /h	120 m ³ /h	250 m ³ /h
Pumping speed at 60 Hz	2.9 m ³ /h	36 m ³ /h	70 m ³ /h	144 m ³ /h	300 m ³ /h
Ultimate pressure without gas ballast	≤6·10 ⁻³ mbar	≤3·10 ⁻³ mbar		3·10 ⁻³ mbar	
Ultimate pressure with gas ballast	≤6·10 ⁻³ mbar	≤5·10 ⁻³ mbar		6·10 ⁻³ mbar	5·10 ⁻³ mbar
Weight	10.5 kg	56 kg	65 kg	205 kg	360 kg

*without magnetic coupling

PentaLine™

Two-stage rotary vane pumps – space-saving and cost-effective.



Analytics

Research & Development

Industry





PentaLine™

Applications

- ▶ Freeze drying
- ▶ Metallurgy
- ▶ Mass spectrometry
- ▶ Electron microscopy
- ▶ Leak detection
- ▶ Gas analysis
- ▶ Research & Development
- ▶ Coating

Advantages at a glance

- ▶ Standby mode – Longer service life, intelligent process control
- ▶ Power-saving – Lower operating costs (-50%), environmentally friendly
- ▶ Worldwide power supply – Simple logistics, connects to all standard power supply systems
- ▶ Lowest switch-on current – Easy system integration, cost reduction
- ▶ Hermetically sealed – No oil leakage, significantly improved leak rate versus conventional rotary vane pumps
- ▶ Runs cooler – Gives off less heat in standard operation

Technical data

Rotary vane pumps	Penta 10	Penta 20	Penta 35
Pumping speed max.	11 m ³ /h	22 m ³ /h	34 m ³ /h
Ultimate pressure, without gas ballast	≤ 5 · 10 ⁻³ mbar		
Ultimate pressure, with gas ballast	≤ 1 · 10 ⁻² mbar		
Weight with motor	42 kg	43 kg	45 kg

OktaLine™

Just right for every low and medium vacuum application.



Metallurgy



Electron beam welding



Packaging industry





OktaLine™

Applications

- ▶ Metallurgy
- ▶ Simulation chambers
- ▶ Packaging industry
- ▶ Freeze/vacuum drying
- ▶ Thin-film technology
- ▶ Electron beam welding
- ▶ Load-locks/transfer chambers
- ▶ Chemical and process technology
- ▶ Industrial leak detection systems

Advantages at a glance


- ▶ Optimum flexibility and maximum process suitability, thanks to a complete range of Roots pumps
- ▶ Broad range of pumping speeds: 250 to 25,000 m³/h
- ▶ Rugged, compact design
- ▶ Fast evacuation thanks to high compression ratio and overflow valve
- ▶ Maintenance free, maximum reliability and highest uptime thanks to magnetic coupling
- ▶ Low operating costs thanks to air cooling and magnetic coupling
- ▶ Explosion-protected series ADx and ADEx available
- ▶ Operation with frequency converter possible

Technical data

Roots pumps	Okta 250	Okta 500	Okta 1000	Okta 2000	Okta 4000	Okta 6000	Okta 8000	Okta 18000
Nominal pumping speed	270 m ³ /h	490 m ³ /h	1,070 m ³ /h	2,065 m ³ /h	4,050 m ³ /h	6,075 m ³ /h	8,000 m ³ /h	17,850 m ³ /h
Leak rate:								
Pumps with shaft sealing	1 · 10 ⁻² mbar l/s						1 · 10 ⁻² mbar l/s	
Magnetically coupled pumps	1 · 10 ⁻⁵ mbar l/s						-	
Rotation speed (standard motor)	3,000 1/min						1,500 1/min	
Weight	95 kg	125 kg	250 kg	370 kg	600 kg	850 kg	1,550 kg	3,300 kg

CombiLine™

Offering a broad range of Roots pumping stations.



Leak detection



Metallurgy



Coating





**CombiLine™ WU –
with HenaLine™/UnoLine™ Plus**

Applications

- ▶ Load-locks/transfer chambers
- ▶ Helium leak detection
- ▶ Metallurgy
- ▶ Vacuum drying and degassing

CombiLine™ WD – with DuoLine™

Applications

- ▶ Coating
- ▶ Metallurgy
- ▶ Solar cell production
- ▶ Vacuum drying



CombiLine™ WH – with HeptaDry™

Applications

- ▶ Coating
- ▶ Metallurgy
- ▶ Vacuum drying
- ▶ Degassing of plastics

Advantages at a glance

- ▶ Standard pumping stations and customer-specific solutions
- ▶ Support in designing your vacuum system
- ▶ Magnetically coupled pumping stations available – hermetically tight and maintenance-free

Technical data

Pumping station	CombiLine™ WU	CombiLine™ WD	CombiLine™ WH
Roots pump	Okta 250 – 6000	Okta 250 – 4000	Okta 250 – 6000
Backing pump	Hena 60 – 1000	DUO 35 – 255	HeptaDry™ 100 – 600
Pumping speed at 1 mbar	230 – 5,300 m ³ /h	220 – 3,000 m ³ /h	240 – 4,900 m ³ /h
Final pressure	< 3 · 10 ⁻² mbar*	< 3 · 10 ⁻⁴ mbar*	< 2 · 10 ⁻³ mbar**
Weight	210 – 2,300 kg	190 – 1,100 kg	300 – 1,900 kg

* without gas ballast
** 50 Hz

XtraDry™ · Diaphragm pumps (MVP) · HeptaDry™

Universal dry compressing pumps.



Coating

Metallurgy

Electron beam welding





XtraDry™ – Piston pumps

Applications

- ▶ Mass spectrometry
- ▶ Leak detection
- ▶ Electron microscopes
- ▶ Vacuum packaging

Advantages at a glance

- ▶ Gas independent pumping characteristics – No gas backstreaming in the pumping system
- ▶ Particle-free – No process contamination
- ▶ Hydrocarbon-free – Oil-free pumping system

Diaphragm pumps (MVP)

Applications

- ▶ Research & development
- ▶ Laboratories
- ▶ Analytical industry
- ▶ Suited as a backing pump for Pfeiffer Vacuum turbopumps

Advantages at a glance

- ▶ Absolutely oil-free vacuum
- ▶ Long diaphragm service life
- ▶ Compact and light
- ▶ Low noise and vibration levels



HeptaDry™ – Screw pumps

Applications

- ▶ Metallurgy
- ▶ Coating
- ▶ Freeze-drying
- ▶ Load-locks
- ▶ Electron beam welding

Advantages at a glance

- ▶ Complete series of pumps with pumping speeds from 100 to 600 m³/h
- ▶ Optimum ultimate pressure and broadest range of applications
- ▶ Absolutely dry and oil-free
- ▶ Water cooling with thermostatic valve
- ▶ Low energy consumption, low noise level

Technical data

Dry pumps	XtraDry™ 150 / 250 Piston pumps	MVP 006 – 160 Diaphragm pumps	HeptaDry™ 100 – 600 Screw pumps
Ultimate pressure: Total without gas ballast	< 0.1 / < 7 mbar	< 5 · 10 ⁻¹ – < 4 mbar	< 0.05 mbar
Nominal pumping speed	7.5 / 13 m ³ /h	0.288 m ³ /h – 9.6 m ³ /h	110 – 525 m ³ /h
Leak rate	< 0.01 mbar l/s	6 · 10 ⁻² – 1 mbar l/s	–
Rotational speed	–	1,500 – 3,000 1/min	3,000 1/min
Weight	30 kg	1.8 – 25 kg	250 – 690 kg

OnTool™ Booster

The high-vacuum pump that works against atmosphere.



Coating



Load-lock of solar cell coating system¹⁾



Wafer fabrication





OnTool™ Booster

Applications

- ▶ Transfer chambers
- ▶ Load-locks
- ▶ EUV lithography
- ▶ Solar cell coating
- ▶ Optical coating
- ▶ Surface finishing
- ▶ Simulation chambers

Advantages at a glance


- ▶ Innovative – High-vacuum directly against atmosphere
- ▶ Cost-effective – No backing pump required
- ▶ Compact – Can be connected directly to the tool
- ▶ Particle-free – For all clean applications
- ▶ Flexible – Can be used as either a stand-alone or backing pump
- ▶ Short cycle times – Optimized for a low transfer pressure
- ▶ Powerful – Very high pumping speed of 130 m³/h
- ▶ Flexible high-vacuum flange position

Technical data

Side channel pump	OnTool™ Booster
Max. pumping speed for N ₂ :	
At 10 ⁻¹ mbar (75 mTorr) inlet pressure	130 m ³ /h
At atmospheric inlet pressure	18 m ³ /h
Ultimate pressure	< 10 ⁻⁵ mbar
Rotation speed	60,000 1/min
Weight	35 kg

HiPace™ · HiPace™ MC

Dependable operation. Low cost of ownership.
Wide variety of applications.



Wafer fabrication

Mass spectrometry

Semiconductor

Plasma physics





HiPace™



Applications

- ▶ Electron microscopy
- ▶ Ion implantation
- ▶ Film coating
- ▶ Particle accelerators
- ▶ Electron beam welding
- ▶ Lamp/tube manufacturing

Advantages at a glance

- ▶ Compact series of pumps with pumping speeds from 10–2,000 l/s
- ▶ Robust engineering and proven bearing system offer maximum reliability
- ▶ High gas throughputs and high pumping speeds
- ▶ Integrated, powerful cooling
- ▶ Corrosive gas version available



HiPace™ MC

Applications

- ▶ Ion beam etching
- ▶ Ion implantation
- ▶ Space simulation
- ▶ Solar cell coating
- ▶ Metallurgy

Advantages at a glance

- ▶ Integrated drive electronics eliminate the need for cumbersome and costly cabling
- ▶ Suitable for most applications thanks to high pumping speed and high gas throughput
- ▶ Extremely low vibration and noise for sensitive applications
- ▶ Highly reliable thanks to permanent rotor monitoring


MC = magnetically levitated and suitable for corrosive gases

Technical data

Pump model	HiPace™ 10–700	HiPace™ 1200–2300	HiPace™ 2400 / 3400 MC
Pumping speed N ₂	10–685 l/s	1,250–1,900 l/s	2,100–2,950 l/s
Compression N ₂	3 · 10 ⁵ –> 1 · 10 ¹¹ mbar	> 1 · 10 ⁹ mbar	> 1 · 10 ⁹ mbar
Rotation speed	90,000–49,200 1/min	37,800–31,500 1/min	29,400–24,000 1/min
Weight	1.8–17.4 kg	27–47 kg	71–94 kg

HiCube™ Eco · HiCube™ Classic · HiCube™ Pro

The complete solution for high vacuum applications.



Accelerators

Vacuum furnaces

Glass coater





HiCube™ Eco

Applications

- ▶ Laboratory applications
- ▶ Spectroscopy
- ▶ Surface analysis
- ▶ Small coating systems
- ▶ Leak detection
- ▶ Tube manufacturing

Advantages at a glance

- ▶ Plug & play pumping station
- ▶ Flexible design
- ▶ Dry high-vacuum pump system with turbo and diaphragm pump
- ▶ Versatile accessories
- ▶ Display control unit with integrated gauge connection



HiCube™ Classic / Pro

Applications

- ▶ Research & development
- ▶ Accelerators
- ▶ Analytics and surface analysis
- ▶ Vacuum process engineering
- ▶ Electron beam welding
- ▶ Leak detection systems

Advantages at a glance

- ▶ Optimally inter-coordinated combination of turbopump and backing pump; for the widest range of applications
- ▶ Modular design affords simple customization for the application in question
- ▶ Service friendly, due to good accessibility of the individual components
- ▶ Integrated drive electronics; no additional control system needed

Technical data

Turbo pumping stations	HiCube™ Eco	HiCube™ Classic	HiCube™ Pro
Pumping speed N ₂	35 – 67 l/s	35 – 685 l/s	35 – 685 l/s
Pumping speed backing pump	0.9 m ³ /h	0.9 – 5 m ³ /h	7.5 – 34 m ³ /h
Final pressure	< 1 · 10 ⁻⁷ mbar	< 1 · 10 ⁻⁷ – < 5 · 10 ⁻¹⁰ mbar	< 1 · 10 ⁻⁷ – < 5 · 10 ⁻¹⁰ mbar
Weight	17 kg	31.5 – 60.5 kg	69.2 – 100.7 kg

Components and feedthroughs

For all vacuum applications.



Pumping station



Inline coating system



Pumping station





Components

- ▶ Connection components
- ▶ Seals
- ▶ Flanges
- ▶ Pipe components
- ▶ Bellows
- ▶ Adapters
- ▶ ISO-KF, ISO-K, CF

Feedthroughs

- ▶ Rotary feedthroughs
- ▶ Linear feedthroughs
- ▶ Rotary/linear feedthroughs
- ▶ Liquid feedthroughs
- ▶ Sight glasses
- ▶ Electrical feedthroughs
- ▶ Coaxial feedthroughs
- ▶ ISO-KF, ISO-K, CF

Technical data

Components	
Nominal diameter	DN 10 – DN 1000
Material	Aluminum, steel, stainless steel
Seal	Neoprene, aluminum, copper, copper silver plated, FPM

Feedthroughs	Nominal diameter	Connector	
Rotary feedthroughs	DN 16 – DN 63	ISO-KF, ISO-K, CF	Torque: 0.4 – 500 Nm
Linear feedthroughs	DN 16 – DN 40	CF	Stroke: 25 – 50 mm
Rotary/linear feedthroughs	DN 16 – DN 40	ISO-KF	Stroke: 50 – 150 mm
Liquid feedthroughs	DN 40	ISO-KF, CF	Temperature range: -200 °C to +400 °C
Sight glasses	DN 16 – DN 160	ISO-KF, ISO-K, ISO-F, CF	Glasses: Borosilicate, Kodial, Sapphire
Electrical feedthroughs	DN 16 – DN 40	ISO-KF, CF	Voltage: up to 12 kV Current: up to 1,500 A

Valves

For shutting off, venting and dosing.



Coating systems



Leak detection systems





Valves

- ▶ Angle valves
- ▶ Inline valves
- ▶ Gate valves
- ▶ Bellows-sealed gate valves
- ▶ Mini angle valves
- ▶ Mini inline valves
- ▶ Regulation valves
- ▶ ISO-KF
- ▶ ISO-K
- ▶ CF
- ▶ ISO-F

Technical data

Valves	
Nominal diameter	DN 5–DN 250
Pressure ranges	$1 \cdot 10^3 - 1 \cdot 10^{-11}$ mbar
Seal	FPM, Aluminum, copper
Housing	Stainless steel, aluminum
Actuation	Manually, electropneumatically, electromagnetically

DigiLine™ · ActiveLine · ModulLine



Total pressure measurement





DigiLine™

Total pressure measurement with digital signal output.

Advantages at a glance

- ▶ Reliable data transfer through digital signals
- ▶ Serial interface RS 232/485 selectable
- ▶ Five different transmitters and two control units available

Technical data

Gauges	DigiLine™
Measurement range	$1 \cdot 10^{-9}$ – 2,000 mbar
Measuring cycle	40 ms

Gauges	ActiveLine
Measurement range	$5 \cdot 10^{-11}$ – 55,000 mbar
Pressure max.	2 – 15 bar

Gauges	ModulLine
Measurement range	$1 \cdot 10^{-11}$ – 1,000 mbar
Bakeout temperature	150 – 250 °C



ActiveLine

Vacuum measurement with analog signal output.

Advantages at a glance

- ▶ Compact design
- ▶ Easy integration
- ▶ Cost-effective
- ▶ Ceramic technology sensor
- ▶ Pressure reading independent of gas type
- ▶ Eight transmitters and three control units available

ModulLine

Vakuummessung in radioaktiver Umgebung.

Advantages at a glance

- ▶ Rugged and well proven design
- ▶ Basically unaffected by radioactivity and electromagnetic fields
- ▶ Is being used on all large accelerators
- ▶ Four different interface options (Profibus)

SmartTest

The ingenious solution to your quality assurance.



Automotive
industry

Semiconductor production

Solar cell production

Refrigeration, air conditioning





SmartTest

Applications

- ▶ Automotive industry
- ▶ Semiconductor production
- ▶ Lamp manufacturing
- ▶ Refrigeration, air conditioning
- ▶ Coating

Advantages at a glance

- ▶ Maximum sensitivity for detecting even minute leaks
- ▶ One-button operation – Ultra-simple handling
- ▶ Robust engineering – Reliable and long-lived
- ▶ Modular design – Application-specific solutions possible
- ▶ Pfeiffer Vacuum turbopump – Maximum inlet pressure 25 mbar, extremely short recovery times

Technical data

Leak detector	SmartTest HLT 550–575
Smallest detectable leak rate for He	$< 5 \cdot 10^{-12}$ mbar l/s
Test method	Vacuum and sniffing leak detection
Detectable gases	^4He , ^3He , H_2
Response time	0.5 s
Pumping speed for He	2.5 l/s
Inlet pressure max.	25 mbar
Available backing pumps	Rotary vane, diaphragm and scroll pumps as well as XtraDry™

PrismaPlus™ · HiQuad™ · OmniStar™ · ThermoStar™

For gas analysis.



Accelerator

Coating

Research & Development





PrismaPlus™

Advantages at a glance

- ▶ Modular design offers optimum adaptability
- ▶ Compact size yet high performance
- ▶ A variety of interfaces make for simple systems integration
- ▶ High measurement speed, stability and resolution
- ▶ Interchangeability of analyzers and electronics
- ▶ Intuitive operation of the Quadera® software
- ▶ Mass ranges 1–100 amu, 1–200 amu, 1–300 amu

HiQuad™

Advantages at a glance

- ▶ Modular, flexible design
- ▶ Simple operation with Quadera® software
- ▶ Extremely high measurement speed
- ▶ Maximum sensitivity and wide dynamic range
- ▶ Outstanding long-term stability
- ▶ Ethernet interface
- ▶ Integral Internet browser and OPC server for communicating with PC-based programs



OmniStar™

Advantages at a glance

- ▶ Quantitative gas analysis – inclusive non-polar molecules, inert gases, etc.
- ▶ Low detection threshold (< 1 ppm) even for condensable gases
- ▶ Temperature-controlled gas line (stainless steel capillary)
- ▶ Control of up to 64 gas components
- ▶ Short response time
- ▶ Online process control
- ▶ Mass ranges 1–100 amu, 1–200 amu, 1–300 amu

ThermoStar™

Advantages at a glance

- ▶ Reactive and condensable gases are detectable even in small concentrations
- ▶ Temperature-controlled gas line (quartz capillary)
- ▶ No chemical reaction
- ▶ Certain identification of unknown gases
- ▶ Mass ranges 1–100 amu, 1–200 amu, 1–300 amu

Helium leak detection systems

Best-in-class technology for your quality assurance.



Leak detection systems





Helium leak detection systems

Applications

- ▶ Automotive industry
(e.g. airbags, aluminum rims, fuel tanks system assemblies, air conditioning and air suspension system components)
- ▶ Refrigeration/air conditioning technology
(e.g. evaporators, compressors)
- ▶ Vacuum and pressurization technology
(e.g. valves and fittings)
- ▶ Packaging technology
(e.g. for pharmaceutical products, foods)

Advantages at a glance

- ▶ Optimum sensitivity in detecting even the smallest leaks
- ▶ Dry testing instead of bubble testing
- ▶ Automated measurement method
- ▶ Minimizes testing times and operating costs
- ▶ Compliance with quality and environmental requirements
- ▶ Fully automated test procedure

Vacu²

The revolution in die casting!



From raw material ...

... to final products





Visual comparison of a conventional vacuum process (left hand) with Vacu² from Pfeiffer Vacuum (right hand) following glow test at 500 °C

Vacu²

Application

- ▶ Die casting

Advantages at a glance

- ▶ Better vacuum translates into optimum quality
- ▶ Reliable process monitoring reduces the rejection rate
- ▶ Faster process optimization and better designed molds as low as vent valves reduce your costs

Technical data

Vacuum System	Vacu ²
Pumping speed	200 m ³ /h
Achievable ultimate pressure in buffer recipient	5 mbar
Footprint	
Dimensions (W x D x H)	1,300 x 930 x 3,716 ¹⁾ mm
Weight	1,000 kg
Electrical connection data	
Rating	7.2 kVA
Frequency	50 Hz / 60 Hz
Voltage	3 x 400 V / 3 x 208 V
Control voltage	24 VDC

¹⁾ Variable, depending upon recipient

Service and Training





First-class service and training for high-quality products. Responsive. Dependable. Cost-effective.

Pfeiffer Vacuum offers a comprehensive service and training program.

Service

Advantages at a glance

- ▶ Fast, competent service worldwide
- ▶ On-site bearing replacement for turbopumps
- ▶ Repairs, exchange products and spare parts
- ▶ Custom-tailored service agreements
- ▶ Leak detection service
- ▶ On-site start-up of components and systems

Training

Advantages at a glance

- ▶ Customer-specific training on-site at your facility or at the Training Center in Asslar
- ▶ Comprehensive training program worldwide:
 - Fundamentals of vacuum technology
 - Vacuum pumps
 - Vacuum measurement
 - Leak detection
 - Mass spectrometry

Leading innovations. Too fast to be copied.

Pfeiffer Vacuum – A name that stands for reliable high-tech products and innovative solutions that support our customers in their applications and pave the way to their success.

Our vacuum technology developments always keep us a step ahead!



All data subject to change without prior notice. PI 0207 PE (March 2010/0)



More Information for You?

Please mark with a cross and return by reply card or fax.



Please return by fax to: +49 (0) 6441 802-202

- Yes, I want more information to the following products marked with a cross.
Please send me a brochure.
- HenaLine™ CombiLine™ OnTool™ Booster PrismaPlus™
- PentaLine™ XtraDry™ HiPace™ Vacu²
- OktaLine™ HeptaDry™
- Please send me the new **general catalog „Vacuum Technology Book“**

My branch of business:

- Analytics Research & Development
- Coating Semiconductor
- Chemical and Process Technology Industry
- Other:

Further information on the internet: www.pfeiffer-vacuum.net

Sender

- Name:
- Company:
- Address:
- Zip code/City:
- Country:
- Phone/E-mail:



More Information for You?

Please mark with
a cross and return by
reply card or fax.



Reply card

Please
frank

Reply to

Pfeiffer Vacuum GmbH
Marketing
Berliner Strasse 43
35614 Asslar
Germany